



GR533x Reliability Test Report

Version: 1.0

Release Date: 2024-04-01

Copyright © 2024 Shenzhen Goodix Technology Co., Ltd. All rights reserved.

Any excerpt, backup, modification, translation, transmission or commercial use of this document or any portion of this document, in any form or by any means, without the prior written consent of Shenzhen Goodix Technology Co., Ltd. is prohibited.

Trademarks and Permissions

GOODIX and other Goodix trademarks are trademarks of Shenzhen Goodix Technology Co., Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Disclaimer

Information contained in this document is intended for your convenience only and is subject to change without prior notice. It is your responsibility to ensure its application complies with technical specifications.

Shenzhen Goodix Technology Co., Ltd. (hereafter referred to as “Goodix”) makes no representation or guarantee for this information, express or implied, oral or written, statutory or otherwise, including but not limited to representation or guarantee for its application, quality, performance, merchantability or fitness for a particular purpose. Goodix shall assume no responsibility for this information and relevant consequences arising out of the use of such information.

Without written consent of Goodix, it is prohibited to use Goodix products as critical components in any life support system. Under the protection of Goodix intellectual property rights, no license may be transferred implicitly or by any other means.

Shenzhen Goodix Technology Co., Ltd.

Headquarters: Floor 12-13, Phase B, Tengfei Industrial Building, Futian Free Trade Zone, Shenzhen, China

TEL: +86-755-33338828 Zip Code: 518000

Website: www.goodix.com

Preface

Purpose

This document introduces GR533x family reliability qualification results, to help users understand the reliability performance of this product.

Audience

This document is intended for:

- Device user
- Hardware developer
- Tester

Release Notes

This document is the *GR533x Reliability Test Report*, corresponding to GR533x SoC.

Revision History

Version	Date	Description
1.0	2024-04-01	Initial release

Contents

Preface..... I

1 Introduction..... 1

2 Reliability Test Items and Results.....2

 2.1 Electrostatic Discharge: Human Body Model (HBM)..... 2

 2.2 Electrostatic Discharge: Charged Device Model (CDM)..... 2

 2.3 Latch Up (LU).....3

 2.4 High Temperature Operating Life Test (HTOL)..... 3

 2.5 Pre-Conditioning (Pre-Con).....4

 2.6 Temperature Cycling Test (TCT).....4

 2.7 Highly Accelerated Temperature and Humidity Stress Test (HAST).....5

 2.8 Unbiased Highly Accelerated Temperature and Humidity Stress Test (UHAST)..... 5

 2.9 High Temperature Storage Test (HTST)..... 5

1 Introduction

The Goodix GR533x family is a single-mode, low-power Bluetooth 5.3 System-on-Chip (SoC). This report aims to provide a detailed description of the methods used to verify that the product under test meets Goodix stringent quality and reliability requirements. Each test is described and the results are presented. The evaluations done for this qualification are included in the following sections.

2 Reliability Test Items and Results

2.1 Electrostatic Discharge: Human Body Model (HBM)

Table 2-1 Test requirements

Reference Standard	ESDA/JEDEC JS-001
Test Parameter	I-V Curve / Function Test
Model	Human Body Model
Test Conditions	RP=1.5 k Ω , C=100 pF Power to Power (+/-) IO to Power (+/-) IO to IO (+/-)
Sample Size	3 units per mode
Accept Criteria	0 Fail

Table 2-2 Test results

Test Point	Result
± 2000 V/Class 2	PASS

2.2 Electrostatic Discharge: Charged Device Model (CDM)

Table 2-3 Charged Device Model test requirements

Reference Standard	ESDA/JEDEC JS-002
Test Parameter	I-V Curve / Function Test
Model	Charged Device Model
Test Conditions	RP=0 Ω , C=0 pF All pin (+/-) to common ground
Sample Size	3 units per mode
Accept Criteria	0 Fail

Table 2-4 GR5332 Test results

Test Point	Result
± 500 V/ Class C2a	PASS

Table 2-5 GR5331 Test results

Test Point	Result
±400 V/ Class C1	PASS

2.3 Latch Up (LU)

Table 2-6 Latch up test requirements

Reference Standard	JESD-78
Test Parameter	I-V Curve / Function Test
Model	Current / Voltage Trigger
Test Conditions	I Trigger / Over Voltage, Class I
Sample Size	3 units per mode
Accept Criteria	0 Fail

Table 2-7 Test results

Test Point	Result
±200 mA	PASS
1.5*Vcc Max or MSV	PASS

2.4 High Temperature Operating Life Test (HTOL)

Table 2-8 Test requirements

Reference Standard	JESD22-A108
Test Parameter	Function Test
Model	Arrhenius model for temperature acceleration factor and voltage $AF = \exp[\gamma_v * (V_{stress} - V_{op})] * \exp\left[\frac{Ea}{K} \left(\frac{1}{T_{op}} - \frac{1}{T_{stress}}\right)\right]$
Test Conditions	125°C, 1000 hrs., VCCmax
Sample Size	77 units*3 Lot
Accept Criteria	0 Fail

Table 2-9 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
168 hrs.	PASS	PASS	PASS

Time Point	Result		
	Lot1	Lot2	Lot3
500 hrs.	PASS	PASS	PASS
1000 hrs.	PASS	PASS	PASS

2.5 Pre-Conditioning (Pre-Con)

Table 2-10 Test requirements

Reference Standard	JESD22-A113
Test Parameter	Function Test / Appearance Inspection
Model	None
Test Conditions	Baking 125°C 24hrs., Soaking 30°C /60% RH 192 hrs., 3x reflow.
Sample Size	75 units*3 Lot
Accept Criteria	0 Fail

Table 2-11 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
Pre-con Over.	PASS	PASS	PASS

2.6 Temperature Cycling Test (TCT)

Table 2-12 Test requirements

Reference Standard	JESD22-A104
Test Parameter	Function Test / Appearance Inspection
Model	None
Test Conditions	-65 °C to 150 °C, 500 cycles
Sample Size	25 units*3 Lot
Accept Criteria	0 Fail

Table 2-13 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
500 cycles	PASS	PASS	PASS

2.7 Highly Accelerated Temperature and Humidity Stress Test (HAST)

Table 2-14 Test requirements

Reference Standard	JESD22-A110
Test Parameter	Function Test / Appearance Inspection
Model	None
Test Conditions	130 °C, 85% RH, Vcc Max, 96 hrs.
Sample Size	25 units*3 Lot
Accept Criteria	0 Fail

Table 2-15 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
96 hrs.	PASS	PASS	PASS

2.8 Unbiased Highly Accelerated Temperature and Humidity Stress Test (UHAST)

Table 2-16 Test requirements

Reference Standard	JESD22-A118
Test Parameter	Function Test / Appearance Inspection
Model	None
Test Conditions	130 °C, 85% RH, 96 hrs.
Sample Size	25 units*3 Lot
Accept Criteria	0 Fail

Table 2-17 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
96 hrs.	PASS	PASS	PASS

2.9 High Temperature Storage Test (HTST)

Table 2-18 Test requirements

Reference Standard	JESD22-A103
Test Parameter	Function Test / Appearance Inspection
Model	None
Test Conditions	150 °C, 1000 hrs.

Sample Size	25 units*3 Lot
Accept Criteria	0 Fail

Table 2-19 Test results

Time Point	Result		
	Lot1	Lot2	Lot3
500 hrs.	PASS	PASS	PASS
1000 hrs.	PASS	PASS	PASS